US Army Corps
of Engineers

MISCELLANEOUS PAPER CERC-88-15

WAVE REFRACTION AT COOS BAY, OREGON

Coastal Model Investigation

by

Ernest R. Smith

Coastal Engineering Research Center

DEPARTMENT OF THE ARMY

Waterways Experiment Station, Corps of Engineers
PO Box 631, Vicksburg, Mississippi 39181-0631

October 1988

Final Report

Approved For Public Release; Distribution Unlimited

Prepared for US Army Engineer District, Portland
PO Box 2946, Portland, Oregon 97208-2946

Destroy this report when no longer needed. Do not return
it to the originator.

The findings in this report are not to be construed as an official
Department of the Army position unless so designated
by other authorized documents.

The contents of this report are not to be used for
advertising, publication, or promotional purposes.
Citation of trade names does not constitute an
official endorsement or approval of the use of
such commercial products.

Unclassified
SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No 0704-0188 Exp Date Jun 30 1986	
1a REPORT SECURITY CLASSIFICATION Unclassified			1b RESTRICTIVE MARKINGS		
2a SECURITY CLASSIFICATION AUTHORITY			3 DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited.		
2b DECLASSIFICATION/DOWNGRADING SCHEDULE			5 MONITORING ORGANIZATION REPORT NUMBER(S)		
4 PERFORMING ORGANIZATION REPORT NUMBER(S) Miscellaneous Paper CERC-88-15			7a NAME OF MONITORING ORGANIZATION		
6a NAME OF PERFORMING ORGANIZATION USAEWES, Coastal Engineering Research Center		6b OFFICE SYMBOL (If applicable) CEWES-CW-P		7b ADDRESS (City, State, and ZIP Code)	
6c ADDRESS (City, State, and ZIP Code) PO Box 631 Vicksburg, MS 39181-0631		8a NAME OF FUNDING/SPONSORING ORGANIZATION US Army Engineer District, Portland		9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8b OFFICE SYMBOL (If applicable)		8c ADDRESS (City, State, and ZIP Code) PO Box 2946 Portland, Oregon 97208-2946		10 SOURCE OF FUNDING NUMBERS	
				PROGRAM ELEMENT NO.	PROJECT NO
				TASK NO	WORK UNIT ACCESSION NO
11 TITLE (Include Security Classification) Wave Refraction at Coos Bay, Oregon					
12 PERSONAL AUTHOR(S) Smith, Ernest R.					
13a TYPE OF REPORT Final report		13b TIME COVERED FROM Feb 88 TO Jun 88		14 DATE OF REPORT (Year, Month, Day) October 1988	
				15 PAGE COUNT 28	
16 SUPPLEMENTARY NOTATION Available from National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161.					
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Refraction Storm damage		
			Rubble-mound breakwater Water waves		
19 ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>Coos Bay, Oregon, is protected by two rubble-mound jetties. At present, 500 ft of the north jetty has deteriorated to the extent that structural integrity is threatened. Discussed herein are efforts by the US Army Engineer District, Portland, to restore the jetty, assisted in their efforts by the Coastal Engineering Research Center which has performed a numerical water wave refraction/diffraction/shoaling analysis over the outer bathymetry at Coos Bay to determine wave characteristics.</p>					
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS			21 ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a NAME OF RESPONSIBLE INDIVIDUAL			22b TELEPHONE (Include Area Code)		22c OFFICE SYMBOL

PREFACE

Model investigations of Coos Bay, Oregon, were requested by the US Army Engineer District, Portland (NPP), and conducted by personnel of the US Army Engineer Waterways Experiment Station's (WES's) Coastal Engineering Research Center (CERC) during February to June 1988. The study was under general supervision of Dr. James R. Houston and Mr. Charles C. Calhoun, Jr., Chief and Assistant Chief, CERC, respectively; and under direct supervision of Messrs. C. Eugene Chatham, Jr., Chief, Wave Dynamics Division (CW), and Douglas G. Outlaw, Chief, Wave Processes Branch, CW-P, CERC.

Mr. Ernest R. Smith, Hydraulic Engineer, CW-P, CW, performed the study which involved application of a refraction/diffraction/shoaling numerical simulation model titled Regional Coastal Processes Wave Transformation Model (RCPWAVE) for water wave nearshore transformation. This model was conceived and developed by Mr. Bruce A. Ebersole, Research Hydraulic Engineer, Research Division, CERC. The assistance of Mr. Ebersole is acknowledged with appreciation. The author wishes also to acknowledge Mr. Larry R. Tolliver and Ms. Robin J. Hoban, CW-P, who digitized the grid; Ms. Lee Ann Germany, CW-P, who typed this report; and Ms. Shirley A. J. Hanshaw, Information Products Division, Information Technology Laboratory, WES, who edited this report.

Commander and Director of WES during the study was COL Dwayne G. Lee, EN. Technical Director was Dr. Robert W. Whalin.

CONTENTS

	<u>Page</u>
PREFACE.....	1
CONVERSION FACTORS, NON-SI TO SI (METRIC)	
UNITS OF MEASUREMENT.....	3
PART I: INTRODUCTION.....	4
Background.....	4
Purpose.....	6
PART II: WAVE TRANSFORMATION MODEL.....	7
Study Conditions.....	7
Study Results.....	8
PART III: CONCLUSION.....	9
TABLE 1	
PLATES 1-14	

CONVERSION FACTORS, NON-SI TO SI (METRIC)
UNITS OF MEASUREMENT

Non-SI units of measurement used in this report can be converted to SI
(metric) units as follows:

<u>Multiply</u>	<u>By</u>	<u>To Obtain</u>
feet	0.3048	metres
miles (US statute)	1.609347	kilometres
tons (force)	8896.444	newtons

WAVE REFRACTION AT COOS BAY, OREGON

PART I: INTRODUCTION

Background

1. Coos Bay (Figure 1) is an estuary on the Oregon coast about 200 miles* south of the Columbia River mouth and 445 miles north of San Francisco Bay. The entrance, protected by the rubble-mound jetties, lies between Coos Head on the south and a low sandspit on the north. A 700-ft-wide, 45-ft-deep channel extends between the jetties.

2. The Port of Coos Bay is the second largest in Oregon and one of the largest shipping ports for forest products in the world, but it is not a major general cargo port because of limited ground transportation of the area. Major commodities exported include wood chips, logs, lumber, plywood, veneer, and paper products. Few commodities are imported, receipts being mostly petroleum products and gravel.

3. The north jetty was completed in 1895 and was 9,600 ft long. The outer 600 ft of the jetty subsided soon after completion and was rebuilt twice before 1900. No further repair work was done until 1923. At that time the outer 1,000 ft of the north jetty had sunk 12 to 20 ft below low water. The jetty was restored to design height from 1923 to 1929. A monolith concrete block was placed at the outer end of the jetty in 1930. To maintain the jetty, 236,342 tons of stone were placed in 1939 and 1940. Repairs were made in 1957 and 1958 to 2,870 ft of the jetty extending to the monolith. The repaired section was constructed to a crest elevation of +25 ft mean lower low water (MLLW) with a 30-ft crown width. The outer end had deteriorated to the low water level by 1970 and was repaired at that time to the 1958 dimensions. The work performed in 1970 consisted primarily of filling small, isolated cavities.

4. Currently, 500 ft of the north jetty, from station 78+00 to station 83+00, has deteriorated to the extent that structural integrity of the jetty is threatened. The most critical section has lost 18.5 ft in elevation.

* A table of factors for converting non-SI units of measurement to SI (metric) units is presented on page 3.

Essentially none of the "as built" crest width remains at station 81+76. Damage is predominantly along the channel side of the jetty. Approximately 34,700 tons of stone have been misplaced. In addition, the seaward 473 ft of the jetty no longer exists.

Purpose

5. Since the damaged section of the jetty lies within a relatively high sediment transport zone, even under moderate wave conditions a breach of the jetty would allow sediment to move into the estuary and shoal, eventually increasing channel maintenance costs. The breach would become progressively larger, allowing waves to overtop the structure and travel into the inner harbor, making a viable year-round navigational channel difficult to maintain. Additionally, the livelihood of the communities of Coos Bay and neighboring North Bend would be seriously impacted if reliable navigation facilities could not be maintained.

6. The US Army Engineer District, Portland (NPP), has considered restoring the jetty from station 78+00 to station 83+00 to 1970 dimensions and determining if the seaward 473 ft of the jetty warrants rehabilitation. As a result, NPP has requested that the US Army Engineer Waterways Experiment Station Coastal Engineering Research Center perform a water wave refraction/diffraction/shoaling analysis at high tide elevation to determine wave characteristics at the north jetty. This report discusses the results of that analysis.

PART II: WAVE TRANSFORMATION MODEL

Study Conditions

7. The Regional Coastal Processes Wave Model (RCPWAVE)* was used to transform deepwater waves over the outer Coos Bay bathymetry. The model employs an iterative, finite difference scheme with full refraction, diffraction, and shoaling effects assuming:

- a. Small bottom slopes.
- b. Linear, monochromatic, and irrotational waves.
- c. Negligible wave reflection.
- d. Insignificant energy losses due to bottom friction or wave breaking outside the surf zone.

Because of assumption a, the jetties could not be included in model simulations.

8. A stretched rectangular grid of 60 by 55 cells covering an area 60,000 ft by 38,000 ft was applied to the offshore Coos Bay bathymetry with fine resolution in the nearshore region and coarse resolution offshore for the five interior incident wave angles. Grid spacing in the nearshore region was 500 ft in the x-direction. In the offshore region, grid spacing varied somewhat, stretching from 500 to 2,000 ft beginning at 19,000 to 38,000 ft in the x-direction. Spacing in the y-direction was 1,000 ft throughout the grid. A rectangular grid of 60 by 74 cells covering approximately the same area as the stretched grid was used for the extreme incident wave angles (north and southwest). Grid spacing was 1,000 ft in the alongshore direction and 500 ft in the offshore direction. Both grids were oriented so that the tip of the north jetty was located at alongshore cell number 24 and offshore cell number 24, and the maximum incident wave angle was ± 67.5 deg. The y-direction was approximately parallel to the shoreline of North Spit, and the x-direction was parallel to the jetties.

9. Seven wave directions (north (N), north-northwest (NNW), northwest (NW), west-northwest (WNW), west, west-southwest (WSW), and southwest (SW))

* B. A. Ebersole, M. A. Cialone, and M. D. Prater, 1985, "Regional Coastal Processes Numerical Modeling System; Report 1: RCPWAVE--A Linear Wave Propagation Model for Engineering Use," Technical Report CERC-86-4, US Army Engineer Waterways Experiment Station, Vicksburg, MS.

and six wave periods (7, 9, 11, 13, 15, and 17 sec) were chosen as test conditions based on Pacific coast hindcast, Phase II data from the Wave Information Studies.

Study Results

10. Wave height coefficients (wave height at a grid cell divided by deepwater wave height H/H_0) were determined over an alongshore distance of 20,000 ft and an offshore distance of approximately 37,000 ft in the vicinity of the jetties. Maximum H/H_0 at the toe was 1.05 for a 17-sec period from the west-northwest. Minimum H/H_0 was 0.66 for 13- and 17-sec periods from the southwest. Table 1 lists H/H_0 at the north jetty toe, one grid cell (500 ft) inshore of the toe, and two grid cells (1,000 ft) inshore of the toe for each direction and period. H/H_0 at the three points listed above are plotted versus period for each direction in Plates 1-7.

11. Example vector plots of H/H_0 and direction over the area near the jetty, for selected periods from each direction, are included in Plates 8-14. The entire data set of vector plots and test results is available upon request.

PART III: CONCLUSION

12. Wave height coefficient analysis results indicate that:

- a. Maximum wave heights along the seaward end of the north Coos Bay jetty are a maximum for waves from the west-northwest at a period of 17 sec.
- b. Little variation in the wave height coefficient calculated for each wave period and direction occurs along the damaged section of the existing breakwater.

Analysis results can be combined with hindcast data to estimate recurrence intervals for storm wave conditions along the outer section of the breakwater.

Table 1
Coos Bay Wave Height Coefficients

<u>Direction</u>	<u>Period</u>	<u>H/H_o</u>		
		<u>Toe</u>	<u>-500 ft</u>	<u>-1,000 ft</u>
North	7.0	0.93	0.93	0.92
	9.0	0.87	0.87	0.87
	11.0	0.83	0.84	0.84
	13.0	0.79	0.80	0.81
	15.0	0.76	0.77	0.79
	17.0	0.75	0.77	0.78
NNW	7.0	0.93	0.93	0.93
	9.0	0.89	0.90	0.91
	11.0	0.88	0.89	0.90
	13.0	0.89	0.90	0.91
	15.0	0.91	0.92	0.93
	17.0	0.93	0.94	0.95
NW	7.0	0.93	0.93	0.93
	9.0	0.91	0.91	0.91
	11.0	0.92	0.92	0.92
	13.0	0.94	0.95	0.95
	15.0	0.98	0.98	0.99
	17.0	1.02	1.02	1.03
WNW	7.0	0.93	0.93	0.93
	9.0	0.91	0.91	0.91
	11.0	0.93	0.93	0.93
	13.0	0.96	0.97	0.97
	15.0	1.01	1.01	1.01
	17.0	1.05	1.06	1.06
West	7.0	0.92	0.92	0.92
	9.0	0.89	0.90	0.91
	11.0	0.90	0.91	0.91
	13.0	0.93	0.94	0.94
	15.0	0.97	0.98	0.98
	17.0	1.02	1.03	1.03
WSW	7.0	0.90	0.90	0.90
	9.0	0.84	0.84	0.84
	11.0	0.83	0.83	0.84
	13.0	0.83	0.84	0.84
	15.0	0.85	0.85	0.86
	17.0	0.87	0.88	0.88
SW	7.0	0.80	0.79	0.77
	9.0	0.71	0.72	0.72
	11.0	0.68	0.68	0.69
	13.0	0.66	0.67	0.67
	15.0	0.67	0.68	0.68
	17.0	0.66	0.67	0.68

COOS BAY WAVE HEIGHT COEFFICIENTS

COOS BAY WAVE HEIGHT COEFFICIENTS

COOS BAY WAVE HEIGHT COEFFICIENTS

COOS BAY WAVE HEIGHT COEFFICIENTS

COOS BAY WAVE HEIGHT COEFFICIENTS

COOS BAY WAVE HEIGHT COEFFICIENTS

COOS BAY WAVE HEIGHT COEFFICIENTS

COOS BAY WAVE HEIGHTS AND DIRECTIONS
PERIOD = 15 s
NORTH WAVE DIRECTION

COOS BAY WAVE HEIGHTS AND DIRECTIONS
PERIOD = 11 s
NNW WAVE DIRECTION

COOS BAY WAVE HEIGHTS AND DIRECTIONS
PERIOD = 7 s
NW WAVE DIRECTION

COOS BAY WAVE HEIGHTS AND DIRECTIONS
PERIOD - 17 s
WNW WAVE DIRECTION

COOS BAY WAVE HEIGHTS AND DIRECTIONS
PERIOD = 13 s
WEST WAVE DIRECTION

COOS BAY WAVE HEIGHTS AND DIRECTIONS
PERIOD - 11 s
WSW WAVE DIRECTION

COOS BAY WAVE HEIGHTS AND DIRECTIONS
PERIOD = 13 s
SW WAVE DIRECTION