



US Army Corps
of Engineers

MISCELLANEOUS PAPER CERC-91-3

EAST PASS AND LUDINGTON SAND TRANSPORT DATA COLLECTION PROJECTS: DATA REPORT

by

Julie Dean Rosati, Kathryn J. Gingerich, Nicholas C. Kraus

Coastal Engineering Research Center

DEPARTMENT OF THE ARMY

Waterways Experiment Station, Corps of Engineers

3909 Halls Ferry Road, Vicksburg, Mississippi 39180-6199



July 1991

Final Report

Approved For Public Release; Distribution Unlimited

Prepared for DEPARTMENT OF THE ARMY
US Army Corps of Engineers
Washington, DC 20314-1000

Under Surf Zone Sediment Transport Processes
Work Unit 34321



Destroy this report when no longer needed. Do not return
it to the originator.

The findings in this report are not to be construed as an official
Department of the Army position unless so designated
by other authorized documents.

The contents of this report are not to be used for
advertising, publication, or promotional purposes.
Citation of trade names does not constitute an
official endorsement or approval of the use of
such commercial products.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE July 1991	3. REPORT TYPE AND DATES COVERED Final report		
4. TITLE AND SUBTITLE East Pass and Ludington Sand Transport Data Collection Projects: Data Report			5. FUNDING NUMBERS Work Unit 34321	
6. AUTHOR(S) Julie Dean Rosati Kathryn J. Gingerich Nicholas C. Kraus				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) USAE Waterways Experiment Station Coastal Engineering Research Center 3909 Halls Ferry Road Vicksburg, MS 39180-6199			8. PERFORMING ORGANIZATION REPORT NUMBER Miscellaneous Paper CERC-91-3	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) US Army Corps of Engineers Washington, DC 20314-1000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Available from National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This report is a compilation of data collected during two field data collection projects designed to measure the longshore sand transport rate. The field projects were conducted at East Pass, Florida, in September 1987 and Ludington, Michigan, in September 1988. Portable sand traps were used to make point measurements of longshore sand transport rates, with corresponding measurements of waves and currents. At Ludington, comparisons were made between the streamer traps and Optical Backscatter Sensors (OBS) under similar surf zone conditions. A complete listing of the sand transport rate, wave height and period, longshore current, water level, sand grain size data is presented for each field data collection project.				
14. SUBJECT TERMS See reverse.			15. NUMBER OF PAGES 50	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	

14. (Continued).

East Pass Project, East Pass, Florida
Field experiment
Longshore sand transport
Ludington Project, Ludington, Michigan
Optical Backscatter Sensor
Streamer trap
Surf zone

PREFACE

The investigations described in this report were authorized as part of the Civil Works Research and Development Program by Headquarters, US Army Corps of Engineers (HQUSACE). This study was conducted under the Shore Protection and Restoration Program, Surf Zone Sediment Transport Processes Work Unit 34321, at the Coastal Engineering Research Center (CERC), US Army Engineer Waterways Experiment Station (WES). The HQUSACE Technical Monitors were Messrs. John H. Lockhart, Jr.; John G. Housley; James E. Crews; and Robert H. Campbell.

Data collection for the studies described herein was conducted by CERC during September 1987 (EAST PASS) and September 1988 (LUDINGTON); subsequent data analysis was conducted through December 1990. Dr. Nicholas C. Kraus, Research Division (RD), CERC, was Principal Investigator (PI) of Work Unit 34321 from its inception in September 1986 until September 1988; Ms. Kathryn J. Gingerich, formerly of the Coastal Processes Branch (CPB), RD, was PI from September 1988 until September 1989; and Ms. Julie Dean Rosati, CPB, RD, was PI from September 1989 through final preparation of this report.

Those assisting in data collection for both the EAST PASS and LUDINGTON studies included Messrs. C. Ray Townsend and Jeffery A. Sewell, both of the Prototype Measurement and Analysis Branch, Engineering and Development Division (EDD), CERC, and Mr. William K. Halford, CPB. Mr. John Brandon and Ms. Brenda Dee Grimes, both formerly of the CPB, also participated in the EAST PASS study. Researchers directing part of the data collection at LUDINGTON included Dr. Reginald A. Beach, University of Washington; Mr. Edward B. Hands, Coastal Structures and Evaluation Branch, EDD; and Ms. Jane M. Smith, CPB. Others assisting in data collection at LUDINGTON included Dr. Mark R. Byrnes, formerly of the CPB; Mr. Alan Cialone, Coastal Oceanography Branch (COB), CERC; Mr. Christopher Frye, formerly of the CPB; Ms. Linda S. Lillycrop, COB; Ms. Heidi Pfeiffer, US Army Engineer District (USAED), Chicago; and Mr. Charles Thompson and Mrs. Vicki Thompson, USAED, Detroit.

This report was reviewed by Ms. Smith and Dr. James R. Tallent, CPB. Ms. Carolyn J. Dickson, CPB, prepared the computer-generated figures. The study was performed under the general administrative supervision of Dr. James R. Houston, Chief, CERC; Mr. Charles C. Calhoun, Jr., Assistant Chief, CERC;

Dr. C. Linwood Vincent, Program Manager, Shore Protection and Restoration Program, CERC; and Mr. H. Lee Butler, Chief, RD, CERC.

COL Larry B. Fulton, EN, was Commander and Director of WES during report preparation and publication. Dr. Robert W. Whalin was Technical Director.

CONTENTS

	<u>Page</u>
PREFACE	1
PART I: INTRODUCTION	4
PART II: DESCRIPTION OF THE PROJECTS	7
REFERENCES	13
APPENDIX A: EAST PASS, FLORIDA DATA	A1
APPENDIX B: LUDINGTON, MICHIGAN DATA	B1
APPENDIX C: NOTATION	C1

LIST OF TABLES

<u>No.</u>		<u>Page</u>
1	Values of Sand-Trapping Efficiency for Various Nozzles	11
A1	EAST PASS: Times and Locations of Instrument Deployments	A2
A2	EAST PASS: Sand Dry Weights	A2
A3	EAST PASS: Streamer Elevations from Sea Bed to Mid-Streamer	A3
A4	EAST PASS: Water Levels	A3
A5	EAST PASS: Current Meter Data	A4
A6	EAST PASS: Wave Data	A4
A7	EAST PASS: Profile Survey Data	A5
A8	EAST PASS: Grain Size Statistics	A7
B1	LUDINGTON: Times and Locations of Instrument Deployments	B2
B2	LUDINGTON: Sand Wet Weights	B6
B3	LUDINGTON: Streamer Elevations from Sea Bed to Mid-Streamer	B9
B4	LUDINGTON: Water Levels	B12
B5	LUDINGTON: Current Meter Data	B14
B6	LUDINGTON: Wave Data	B17
B7	LUDINGTON: Profile Survey Data	B19
B8	LUDINGTON: Grain Size Statistics	B23

LIST OF FIGURES

<u>No.</u>		<u>Page</u>
1	Location map for EAST PASS	4
2	Location map for LUDINGTON	5
3	Streamer trap	8
4	Typical SSM arrangement	9
5	Typical TSM arrangement	10
6	Typical CON arrangement	10

EAST PASS AND LUDINGTON SAND TRANSPORT DATA COLLECTION PROJECTS:
DATA REPORT

PART I: INTRODUCTION

1. This report is a compilation of data collected during two field data collection projects performed to measure the longshore sand transport rate in the nearshore zone. The EAST PASS project, a limited deployment designed to test data collection equipment and procedures, was conducted in the Gulf of Mexico, at East Pass, Florida, on 29 September 1987. The EAST PASS project was conducted just south of Eglin Air Force Officer's Club on Santa Rosa Island (Figure 1). The LUDINGTON project was a moderate effort conducted in Lake Michigan, at Ludington State Park, Michigan, from 14 to 21 September 1988. The LUDINGTON project was conducted just south of the lighthouse at Ludington State Park (Figure 2). The objective of these data collection projects was to measure longshore sand transport rates together with the




Figure 1. Location map for EAST PASS




Figure 2. Location map for LUDINGTON

physical factors that produced and controlled the sand movement, including local waves, longshore current, water level, and nearshore bathymetry. This report documents these two projects, including basic sand transport data, current speeds, wave heights and periods, grain size distributions, water levels, and arrangement of instruments during data collection. Reference is also made to sources of related information.

2. This report completes documentation of the longshore sand transport data collection projects conducted by the research work unit "Surf Zone Sediment Transport Processes" (SZSTP) of the Shore Protection and Restoration Program, US Army Engineer Waterways Experiment Station, Coastal Engineering Research Center (CERC). Five longshore sand transport field data collection projects, including the two discussed herein, were conducted from September 1985 through June 1989 under SZSTP. The goal of this field data collection activity was to make comprehensive and high-quality measurements under a wide range of environmental conditions to investigate dependencies of the transport

rate on such factors as sediment grain size, beach slope, and wave and current forcing. Portable sand traps, used to measure longshore sand transport rates, were developed (Kraus 1987) and refined (Rosati and Kraus 1988, 1989, 1991) during the course of the data collection projects. The first two projects, called DUCK85 and SUPERDUCK, were major efforts held in September 1985 and 1986, respectively, at CERC's Field Research Facility in Duck, North Carolina. Documentation, data presentation, and reference to other sources of information for these experiments can be found in Kraus, Gingerich, and Rosati (1989) and Rosati, Gingerich, and Kraus (1990). The third and fourth projects are described herein; selected results of the LUDINGTON project are also given in Rosati et al. (1991). The fifth project was a minor effort that took place in the Pacific Ocean at the Scripps Institution of Oceanography, La Jolla, California, in June 1989. This project was unsuccessful due to unfavorable (confused) surf conditions and instrument fouling by kelp, and therefore will not be documented further.

3. An orientation to the study sites and description of the equipment and methodology used in the projects are given in Part II. Appendices A and B list the EAST PASS and LUDINGTON data, respectively. Appendix C lists the notation used in this report.

PART II: DESCRIPTION OF THE PROJECTS

4. This chapter provides a short explanation of data presented and notation used in Appendices A (EAST PASS) and B (LUDINGTON). For a more complete description of data collection procedures, data analysis, and example results from similar SZSTP field data collection projects, the reader is directed to Kraus (1987); Kraus, Gingerich, and Rosati (1989); and Rosati, Gingerich, and Kraus (1990).

5. The main objective of the SZSTP field data collection projects was to obtain point measurements of longshore sand transport, with simultaneous measurements of waves and currents. The streamer trap, a portable sand trapping apparatus consisting of a vertical array of mesh bags (streamers) mounted on a steel frame, was used to collect sand moving in the nearshore zone during a specified deployment interval (Figure 3). The 0.105-mm mesh bags collect material with nominal grain size greater than the mesh opening. The streamers are attached to the trap frame with stainless steel nozzles and numbered starting with 1 at the bottom. Three-inch Marsh-McBirney electromagnetic current meters, mounted on portable steel tripods, were positioned in close proximity to the traps (slightly downcurrent) (Tables A5 and B5). The x-axis points offshore (positive x-component indicates seaward-directed flow), and the y-axis points alongshore (positive y-component indicates Easterly flow for the EAST PASS data, and southerly flow for the LUDINGTON data) (see Figure 4). The lowered-numbered current meter is typically shoreward of the higher numbered meter. Pressure gages, also mounted on the tripods, were used to measure wave height and period (Tables A6 and B6). Wave and current data were recorded with a portable data logger powered by a generator.

6. Traps were typically deployed for 5- to 10-min intervals. It was determined that this time interval ensured a representative sampling, while preventing excessive scour at the base of the trap's bottom nozzle, which was flush with the bed. Run numbers are a concatenation of the date and local time; for example, Run 8709291125 began on 29 September 1987 at 11:25 am. At LUDINGTON, sand collected in each streamer was weighed in the drip-free wet condition (Table B2), which has been shown to be linearly related to the dry weight (Kraus and Nakashima 1986). Selected samples were taken back to the laboratory, and a relationship between the no-drip wet weight and dry weight




Figure 3. Streamer trap (from Kraus, Gingerich, and Rosati 1989)

determined. For the LUDINGTON samples, the dry weight was determined to be an average of 0.8 times the wet weight. Because of the small number of samples collected at EAST PASS, all were taken back to the laboratory and weighed in a dry state (Table A2). Listings of streamer elevations from seabed to mid-streamer for EAST PASS and LUDINGTON are given in Tables A3 and B3, respectively.

7. As indicated in Tables A1 and B1, four types of sand transport data collection runs were conducted: SSM, TSM, CON, and COM. The Spatial Sampling Method (SSM) consisted of positioning traps across the surf zone (typically out to the breaker line), so that the cross-shore distribution of the long-

shore sand transport rate was measured. Current meters and pressure gages were positioned downdrift of the trap line such that representative waves and currents were measured. An example SSM arrangement is shown in Figure 4.

8. The Temporal Sampling Method (TSM) consisted of repeatedly deploying one or two traps at positions in the nearshore zone to obtain the temporal change in longshore sand transport at a point. The current meters and pressure gages were placed slightly downdrift and inshore of the traps, as shown in a typical TSM setup (Figure 5).

9. Consistency (CON) testing consisted of deploying two traps in close proximity (approximately 1 m apart in both the on-offshore and longshore directions) to obtain a measure of trap reliability and reproducibility under similar wave and current conditions. Similar to the TSM runs, the current meters and pressure gages were positioned slightly downdrift and inshore of the traps (Figure 6).




Figure 4. Typical SSM arrangement (adapted from Kraus, Gingerich, and Rosati 1989)




Figure 5. Typical TSM arrangement (adapted from Rosati, Gingerich, and Kraus 1990)




Figure 6. Typical CON arrangement (Rosati and Kraus 1989)

10. Comparison (COM) runs provided an evaluation of two different sand-transport measuring devices. A streamer trap and another measurement device (either another streamer trap with a different nozzle configuration, or an Optical Backscatter Sensor (OBS)) were positioned in very close proximity, and transport rates compared between devices. If two traps with different nozzle configurations were compared, traps were positioned similar to but slightly closer than in Figure 5. Comparisons between the OBS and streamer trap were conducted either with the OBS mounted on a pipe, positioned close to the trap, or with the OBS mounted directly on the trap frame.

11. Three types of streamer trap nozzles were intercompared at LUDINGTON: D85 (9 cm high by 15 cm wide), SD (2.5 cm high by 15 cm wide, with a 5.1 cm "hood"), and C (5.1 cm high by 5.1 cm wide, with a 5.1 cm hood). The D85 and SD nozzles were named for their use at the DUCK85 and SUPERDUCK field data collection projects, respectively; the C nozzle is abbreviated for its cubic shape. Each nozzle has a different sand-trapping efficiency, depending on its position in the water column, as indicated in Table 1. To obtain accurate estimates of the longshore sand transport rate, sand weights must be divided by the appropriate value of sand-trapping efficiency (Rosati and Kraus 1989). Sand weights presented in Tables A2 and B2 have not been adjusted for nozzle efficiency. Selected samples saved from traps at EAST PASS and LUDINGTON were analyzed to give grain size statistics (Tables A8 and B8, respectively).

12. Bathymetry in the vicinity of the experiment was measured by standard rod-and-level surveys (Tables A7 and B7). Water depths during EAST PASS were visually approximated using the water level on the trap frame (Table

Table 1
Values of Sand-Trapping Efficiency for Various Nozzles
(adapted from Rosati and Kraus 1989)

<u>Nozzle</u>	<u>On-Bed (Streamer 1)</u>	<u>Off-Bed (All Other Streamers)</u>
D85	0.13	0.92
SD	0.68	1.02
C	1.00	1.00

A4). Water level information during the LUDINGTON experiment was obtained from a National Oceanic and Atmospheric Administration (NOAA) gage at LUDINGTON, and is given in meters relative to the International Great Lakes Datum (IGLD) (175.8 m IGLD is referred to as Low Water Datum (LWD)).

13. The data presented herein and in companion reports describing the DUCK85 (Kraus, Gingerich, and Rosati 1989) and SUPERDUCK (Rosati, Gingerich, and Kraus 1990) field data collection projects are intended to provide detailed information of nearshore sand transport as a function of waves and currents. Use of the streamer trap during these field data collection projects facilitated measurements of the vertical distribution of sand transport; across-shore distributions were measured during SSM deployments; and TSM runs allowed the time variation of sand transport at (a) point(s) in the nearshore zone to be evaluated. These measurements together present a two-dimensional representation of nearshore sand transport as it varies through time, and with waves and currents. These data are intended to improve empirical and numerical predictive tools for longshore sand transport, nearshore waves, and nearshore currents. In particular, analytical expressions for vertical, across-shore, and temporal distributions of longshore transport as a function of waves and currents will be incorporated into two- and three-dimensional numerical models of beach change.

14. Future research efforts will be focussed on detailed measurements of surf zone processes in a large laboratory basin at near-prototype scale. The laboratory work will extend the previous field studies, allowing more detailed measurements of processes at a lower cost than would be possible in the field. Additional intercomparison between sediment transport measurement apparatus in the field is recommended, but is not planned at present.

REFERENCES

- Kraus, N. C. 1987. "Application of Portable Traps for Obtaining Point Measurements of Sediment Transport Rates in the Surf Zone," Journal of Coastal Research, Vol 2, No. 2, pp 139-152.
- Kraus, N. C., Gingerich, K. J., and Rosati, J. D. 1989. "DUCK85 Surf Zone Sand Transport Experiment," Technical Report CERC-89-5, US Army Engineer Waterways Experiment Station, Coastal Engineering Research Center, Vicksburg, MS.
- Kraus, N. C., and Nakashima, L. 1986. "Field Method for Determining Rapidly the Dry Weight of Wet Sand Samples," Journal of Sedimentary Petrology, Vol 56, No. 4, pp 550-551.
- Rosati, J. D., Gingerich, K. J., and Kraus, N. C. 1990. "SUPERDUCK Surf Zone Sand Transport Experiment," Technical Report CERC-90-10, US Army Engineer Waterways Experiment Station, Coastal Engineering Research Center, Vicksburg, MS.
- Rosati, J. D., and Kraus, N. C. 1988. "Hydraulic Calibration of the Streamer Trap," Journal of Hydraulic Engineering, Vol 114, No. 12, pp 1527-1532.
- _____. 1989. "Development of a Portable Sand Trap for Use in the Nearshore," Technical Report CERC-89-11, US Army Engineer Waterways Experiment Station, Coastal Engineering Research Center, Vicksburg, MS.
- _____. 1991. "Development of a Portable Sand Trap," Proceedings, Fifth Federal Interagency Sedimentation Conference, Las Vegas, NV.
- Rosati, J. D., Kraus, N. C., Gingerich, K. J., Smith, J. M., and Beach, R. A. 1991. "Distributions of Longshore Sand Transport Measured in Lake Michigan," Proceedings, Coastal Sediments '91, American Society of Civil Engineers.

APPENDIX A: EAST PASS, FLORIDA DATA

Table A1

EAST PASS: Times and Locations of Instrument Deployments

<u>Run ID No.</u>	<u>Instrument</u>	<u>Time CST¹</u>	<u>Type of Run²</u>	<u>Description of Deployment Location</u>
8709291125	T1	1125-1130	TSM	Surf zone, between CM1 and CM2 ↓ 6 m seaward of traps 6 m shoreward of traps
	T2	1130-1135		
	T3	1135-1140		
	T4	1140-1145		
	CM1, PG1	1125-1145		
	CM2, PG2	1125-1145		
8709291524	T1	1524-1529	TSM	Surf zone, between CM1 and CM2 ↓ 3 m seaward of traps 3 m shoreward of traps
	T2	1529-1534		
	T3	1534-1539		
	T4	1539-1544		
	CM1, PG1	1524-1544		
	CM2, PG2	1524-1544		

¹ CST = Central Standard Time.² Notation is defined in Appendix C.

Table A2

EAST PASS: Sand Dry Weights, g

<u>Trap No.</u>	<u>Streamer Number¹</u>					
	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>
<u>Run 8709291125</u>						
1	9.5	9.5	3.6	1.3	0.5	0.3
2	24.4	4.9	4.3	7.5	2.1	0.3
3	15.6	25.5	11.8	8.3	0.2	0.0
4	148.8	62.3	34.7	32.0	16.7	0.0
<u>Run 8709291524</u>						
1	87.1	49.6	44.4	28.8	11.5	2.4
2	195.5	32.3	16.1	15.1	6.3	0.0
3	61.0	40.3	32.7	21.2	3.3	0.7
4	27.9	19.7	13.6	15.2	8.1	0.0

¹ All traps used SD nozzles.

Table A3

EAST PASS: Streamer Elevations from Sea Bed to Mid-Streamer, m

<u>Trap No.</u>	<u>Streamer Number</u>					
	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>
<u>Run 8709291125</u>						
1	0.013	0.083	0.165	0.343	0.533	0.730
2	0.013	0.089	0.191	0.343	0.546	0.743
3	0.013	0.083	0.216	0.375	0.622	0.927
4	0.013	0.089	0.229	0.413	0.546	0.851
<u>Run 8709291524</u>						
1	0.013	0.076	0.171	0.343	0.546	0.724
2	0.013	0.089	0.190	0.343	0.546	0.743
3	0.013	0.095	0.190	0.368	0.546	0.698
4	0.013	0.121	0.216	0.394	0.578	0.781

Table A4

EAST PASS: Water Levels¹

<u>Time Interval</u>	<u>Water Depth</u>
<u>CST</u>	<u>m</u>
<u>Run 8709291125</u>	
1125-1130	0.34
1130-1135	0.45
1135-1140	0.50
1140-1145	0.48
<u>Run 8709291524</u>	
1524-1529	0.55
1529-1534	0.55
1534-1539	0.55
1539-1544	0.58

¹ Water level visually approximated using water surface on trap frame.

Table A5

EAST PASS: Current Meter Data

Time CST ²	Current Speed, cm/sec							
	CY1 ¹		CX1		CY2		CX2	
	Mean	σ_v	Mean	σ_v	Mean	σ_v	Mean	σ_v
<u>Run 8709291125</u>								
1125-1130	-27.1	11.0	4.5	18.6	-26.7	19.4	14.9	34.5
1130-1135	-23.3	12.3	-0.3	18.9	-33.7	21.2	12.0	36.4
1135-1140	-31.3	11.5	4.4	18.4	-35.6	20.0	19.6	34.2
1140-1145	-34.9	11.0	0	20.1	-40.7	20.7	10.7	36.6
<u>Run 8709291524</u>								
1524-1529	-42.2	11.6	6.6	20.7	-36.4	17.4	7.5	32.3
1529-1534	-42.4	12.3	8.1	20.8	-38.5	17.8	10.7	32.4
1534-1539	-37.0	11.5	1.9	21.5	-31.4	21.5	5.2	34.2
1539-1544	-38.2	11.4	5.8	20.7	-32.4	18.4	8.9	32.7

¹ Notation is defined in Appendix C.² Central Standard Time.

Table A6

EAST PASS: Wave Data

Run ID	Gage No.	Averaging	H_{mo} ¹ m	T_p sec
		Interval CST ²		
8709291125	1	1125 - 1145	0.34	5.9
	2	1125 - 1145	0.16	5.9
8709191524	1	1524 - 1544	0.29	4.9
	2	1524 - 1544	0.19	4.9

¹ Notation is defined in Appendix C.² Central Standard Time.

Table A7

EAST PASS: Profile Survey Data

<u>Profile Line No.</u>	<u>Distance from Baseline, m</u>	<u>Elevation, m MLW¹</u>
<u>Run 8709291125²</u>		
2	0.0	1.27
	3.0	1.29
	6.1	1.33
	9.1	1.27
	12.2	1.13
	15.2	0.74
	18.3	0.47
	21.3	0.32
	24.4	0.07
	27.4	-0.22
	30.5	-0.40
	33.5	-0.50
	36.6	-0.52
	39.6	-0.62
	42.7	-0.58
	45.7	-0.53
48.8	-0.50	
51.8	-0.67	
54.9	-0.77	
57.9	-0.90	
61.0	-0.97	
64.0	-1.00	
3	0.0	1.20
	3.0	1.22
	6.1	1.21
	9.1	1.23
	12.2	1.07
	15.2	0.96
	18.3	0.43
	21.3	0.24
24.4	-0.13	
27.4	-0.39	

(Continued)

¹ MLW - Mean Low Water.² Traps located between profile lines 2 and 3; profile lines 2 and 3 were 20 ft apart.

(Sheet 1 of 2)

Table A7 (Concluded)

<u>Profile Line No.</u>	<u>Distance from Baseline, m</u>	<u>Elevation m MLW</u>
	30.5	-0.51
	33.5	-0.62
	36.6	-0.65
	39.6	-0.58
	42.7	-0.61
	45.7	-0.56
	48.8	-0.68
	51.8	-0.81
	54.9	-0.82
	57.9	-0.96
	61.0	-1.07
	64.0	-1.12
<u>Run 8709291524¹</u>		
1A	0.0	1.38
	3.0	1.38
	6.1	1.39
	9.1	1.23
	12.2	0.86
	15.2	0.56
	18.3	0.00
	21.3	-0.07
	24.4	-0.33
	27.4	-0.43
	30.5	-0.50
	33.5	-0.51
	36.6	-0.52
	39.6	-0.42
	42.7	-0.50
	45.7	-0.79
	48.8	-0.95
	51.8	-1.00
	54.9	-1.06

(Sheet 2 of 2)

¹ Traps located at profile line 1A; profile line 1A was midway between profile lines 2 and 3.

Table A8
EAST PASS: Grain Size Statistics

Run ID and Trap No.	Streamer No.	Moment Statistics				Folk Inclusive Graphic Statistics				
		First PHI	Second PHI	Third	Fourth	Median PHI	Mean PHI	Standard Deviation PHI	Skewness	Kurtosis
8709291125 2	1	1.95	0.32	-1.15	10.54	1.96	1.95	0.29	-0.07	1.12
	5	1.82	0.35	-0.59	4.98	1.85	1.84	0.34	-0.11	1.21
8709291524 4	1	1.83	0.34	-1.02	7.97	1.86	1.84	0.32	-0.11	1.19
	5	1.96	0.35	-2.79	25.55	1.98	1.97	0.27	-0.02	1.07

APPENDIX B: LUDINGTON, MICHIGAN DATA

Table B1

LUDINGTON: Times and Locations of Instrument Deployments

Run ID No.	Instrument	Time EDST ¹	Type of Run	Description of Deployment Location
8809141550	T1 ² T2 CM2, PG2 ² CM3, PG3	1550-1555 ↓	Practice	Surf zone 3 m lakeward of T1 Downdrift and opposite T1 Downdrift and opposite T2
8809141610	T3 ² CM2, PG2 ² CM3, PG3 ²	1610-1615 ↓	Practice	Surf zone Downdrift and opposite T3 Downdrift and opposite T3
8809161625	T1 ² T2 T3 ² T4 T5 ² T6 T7 ² CM2, PG2 CM3, PG3 ² PG1	1625-1630 1625-1630 1630-1635 1630-1635 1635-1640 1635-1640 1640-1645 1625-1640 ↓	CON	Surf zone 1 m lakeward of T1 Surf zone 1 m lakeward of T3 Surf zone 1 m lakeward of T5 Surf zone Downdrift and opposite T2, T4, T6 Downdrift and opposite T1, T3, T5, T7 15 m updrift and in line with CM2, PG2
8809161725	T1 ² T2 ² T3 T5 CM2, PG2 CM3, PG3	1725-1730 ↓	SSM	26.9 m from baseline 28.1 m from baseline 30.0 m from baseline 31.5 m from baseline 32.3 m from baseline 30.7 m from baseline
8809171130	T1 ² T2 ² T3 ² T4 T5 T6 T7 CM2, PG2 CM3, PG3 PG1 ²	1130-1135 ↓	SSM	29.2 m from baseline 30.0 m from baseline 33.0 m from baseline 39.1 m from baseline 45.2 m from baseline 57.4 m from baseline 87.9 m from baseline 39.1 m from baseline 45.2 m from baseline 33.0 m from baseline

(Continued)

(Sheet 1 of 4)

¹ EDST = Eastern Daylight Savings Time.² Positioned in surf zone.

Table B1 (Continued)

<u>Run ID</u> <u>No.</u>	<u>Instrument</u>	<u>Time</u> <u>EDST</u>	<u>Type of</u> <u>Run</u>	<u>Description of</u> <u>Deployment Location</u>
8809171521	T1 ¹	1521-1526 ↓	SSM	61.2 m from baseline
	T2 ¹			65.8 m from baseline
	T3 ¹			74.3 m from baseline
	T4			84.5 m from baseline
	T5			90.5 m from baseline
	T6			97.7 m from baseline
	T7			112.7 m from baseline
	CM2, PG2			84.5 m from baseline
	CM3, PG3 PG1 ¹			97.7 m from baseline 65.8 m from baseline
8809181525	T1	1525-1530	TSM (2 pair)	3 m lakeward of T2
	T2 ¹	1525-1530		At breakers
	T3	1530-1535		3 m lakeward of T4
	T4 ¹	1530-1535		At breakers
	T5	1535-1540		3 m lakeward of T6
	T6 ¹	1535-1540		At breakers
	T7	1540-1545		3 m lakeward of breakers
	T8	1545-1550		3 m lakeward of breakers
	CM2, PG2 ¹	1525-1550 ²		Downdrift and opposite T2, T4, T6
	CM3, PG3	↓ ²		Downdrift and opposite T1, T3, T5, T7, T8
	OBS	↓		Updrift and opposite T1, T3, T5, T7, T8
PG1	1525-1545 ²		13 m updrift and midway between PG2 and PG3	
8809181645	T1	1645-1650	TSM (2 pair)	3 m lakeward of T2
	T2 ¹	1645-1650		At breakers
	T3	1650-1655		3 m lakeward of T4
	T4 ¹	1650-1655		At breakers
	T5	1655-1700		3 m lakeward of T6
	T6 ¹	1655-1700		At breakers
	T7	1700-1705		3 m lakeward of T8
	T8 ¹	1700-1705		At breakers
	CM2, PG2 ¹	1650-1715 ²		Downdrift and opposite T2, T4, T6, T8
	CM3, PG3	1650-1715 ²		Downdrift and opposite T1, T3, T5, T7
	OBS	1645-1705		Updrift and opposite T1, T3, T5, T7
PG1	1650-1709		13 m updrift and midway between PG2 and PG3	

¹ Positioned in surf zone.

(Continued)

(Sheet 2 of 4)

² Some gaps exist in data set.

Table B1 (Continued)

<u>Run ID No.</u>	<u>Instrument</u>	<u>Time EDST</u>	<u>Type of Run</u>	<u>Description of Deployment Location</u>
8809191325	T1 ¹	1325-1330	TSM (2 pair)	3 m shoreward of T4
	T2 ¹	1330-1335		3 m shoreward of T5
	T4 ¹	1325-1330		At breakers
	T5 ¹	1325-1330		At breakers
	T6 ¹	1335-1340		3 m shoreward of T7
	T7 ¹	1335-1340		At breakers
	CM2, PG2 ¹	1325-1340		Downdrift and opposite T1, T2, T6
	CM3, PG3 ¹	1325-1340		Downdrift and opposite T4, T5, T7
8809191355	T3 & OBS ¹	1355-1405	COM	Surf zone (OBS mounted on T3)
	CM2, PG2 ¹	1355-1405 ²		Downdrift and opposite T3
	CM3, PG3 ¹	1355-1405 ²		Downdrift and opposite T3
8809191540	T1 ¹	1540-1545	TSM (2 pair)	3 m shoreward of T4
	T2 ¹	1545-1550		3 m shoreward of T5
	T4 ¹	1540-1545		Surf zone
	T5 ¹	1545-1550		Surf zone
	T6 ¹	1550-1555		3 m shoreward of T7
	T7 ¹	1550-1555		Surf zone
	CM2, PG2 ¹	1540-1555		Downdrift and opposite T4, T5, T7
	CM3, PG3 ¹	1540-1555		At breakers
8809191610	T3 & OBS ¹	1610-1615	COM	Surf zone (OBS mounted on T3)
	CM2, PG2 ¹	↓		Downdrift and opposite T3
	CM3, PG3 ¹	∇		Downdrift and opposite T3
8809191645	T3 & OBS ¹	1645-1650	COM	Surf zone (OBS mounted on T3)
	CM2, PG2 ¹	↓		Downdrift and opposite T3
	CM3, PG3 ¹	∇		Downdrift and opposite T3
8809191715	T3 & OBS ¹	1715-1720	COM	Surf zone (OBS mounted on T3)
	CM2, PG2 ¹	↓		Downdrift and opposite T3
	CM3, PG3 ¹	∇		Downdrift and opposite T3

(Continued)

(Sheet 3 of 4)

¹ Positioned in surf zone.² Some gaps exist in data set.

Table B1 (Concluded)

<u>Run ID No.</u>	<u>Instrument</u>	<u>Time EDST</u>	<u>Type of Run</u>	<u>Description of Deployment Location</u>
8809211105	T1 ¹	1105-1110	TSM (1 pair) and COM	At breakers ↓ Downdrift and opposite traps Downdrift and opposite traps
	T2 ¹	1110-1115		
	T3 & OBS ¹	1115-1120		
	T4 ¹	1120-1125		
	T5 ¹	1125-1130		
	T6 ¹	1130-1135		
	T7 ¹	1135-1140		
	CM2, PG2 ¹	1105-1140		
	CM3, PG3	1105-1140		
8809211345	T1 ¹	1415-1420	TSM (1 pair) and COM	At breakers ↓ Downdrift and opposite traps Downdrift and opposite traps
	T2 ¹	1345-1350		
	T3 & OBS ¹	1350-1355		
	T4 ¹	1355-1400		
	T5 ¹	1400-1405		
	T6 ¹	1405-1410		
	T7 ¹	1410-1415		
	CM2, PG2 ¹	1347-1420		
	CM3, PG3	1347-1420		
8809211435	T3 & OBS ¹	1435-1440	COM	Surf zone (OBS mounted on T3) Downdrift and opposite T3 Downdrift and opposite T3
	CM2, PG2 ¹	↓		
	CM3, PG3 ¹	↓		
8809211520	T1 ¹	1520-1525 ↓	SSM and COM	37.0 m from baseline 41.3 m from baseline 45.1 m from baseline 49.7 m from baseline 53.9 m from baseline 57.6 m from baseline 60.7 m from baseline 45.1 m from baseline 54.0 m from baseline
	T2			
	T3 & OBS			
	T4			
	T5			
	T6			
	T7			
	CM2, PG2			
CM3, PG3	1521-1525			

¹ Positioned in surf zone.

Table B2

LUDINGTON: Sand Wet Weights, g

<u>Trap No.</u>	<u>Streamer Number¹</u>				
	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>
<u>Run 8809141550</u>					
1	469.0	76.1	29.7	17.3	6.8
2	61.4	17.6	24.2	18.6	5.8
<u>Run 8809141610</u>					
3	421.4	92.4	29.0	11.4	8.2
<u>Run 8809161625</u>					
1	48.0	116.3	122.0	37.7	17.7
2	64.3	36.5	26.9	14.8	4.6
3	167.3	291.6	138.8	0.0	25.6
4	39.8	15.0	21.2	6.4	6.4
5	141.0	160.3	172.0	55.1	17.5
6	51.9	44.4	21.6	3.0	8.4
7	86.5	111.6	136.2	35.9	8.4
<u>Run 8809161725</u>					
1	262.5	223.6	156.0	22.8	9.9
2	249.7	180.8	143.5	23.3	10.5
3	146.4	213.6	146.0	42.8	13.5
4	45.6	33.4	32.7	15.2	4.6
<u>Run 8809171130</u>					
1	1305.0	598.3	27.0	4.8	10.0
2	1403.7	689.3	242.1	51.4	2.0
3	124.6	160.7	79.1	61.9	16.4
4	14.3	8.0	6.0	4.1	11.9
5	47.3	10.6	3.3	3.3	9.1
6	25.4	8.3	17.5	4.3	4.9
7	63.2	15.2	5.6	8.4	3.5
<u>Run 8809171521</u>					
1	105.7 ²	13.9 ²	8.5 ²	4.5 ²	6.8 ²
2	34.3	5.4	3.9	14.1	2.8
3	181.2	10.6	7.4	0.0	6.5
4	133.1	48.0	4.0	0.0	0.0
5	127.5	5.5	4.9	7.9	0.0
6	18.9	9.6	3.1	8.8	0.0
7	112.3	6.0	4.7	0.0	0.0

(Continued)

¹ Unless otherwise indicated, SD nozzles were used.² C nozzle used.

Table B2 (Continued)

Trap No.	Streamer Number ¹				
	1	2	3	4	5
<u>Run 8809181525</u>					
1	22.2 ²	0.8 ²	1.8 ²	0.4 ²	0.5 ²
2	22.5	9.6	5.6	3.7	6.0
3	50.6	5.1	0.6	3.0	1.7
4	89.6	21.5	13.1	15.4	12.6
5	72.1	54.3	10.1	6.6	3.6
6	191.2	7.7	16.3	3.6	3.7
7	116.2	13.5	5.0	1.9	3.3
8	3.2 ²	15.2 ²	1.6 ²	0.0 ²	0.0 ²
<u>Run 8809181645</u>					
1	24.8 ²	4.2 ²	3.9 ²	1.6 ²	1.6 ²
2	160.2	55.4	71.5	12.3	6.4
3	99.0	0.0	4.9	2.6	3.2
4	150.7	94.0	81.2	15.3	5.5
5	110.7	11.3	6.6	4.9	4.5
6	105.1	136.0	35.3	8.4	5.4
7	24.8	11.9	6.2	5.2	0.0
8	25.3 ²	5.5 ²	7.0 ²	5.3 ²	2.6 ²
<u>Run 8809191325</u>					
1	63.8 ²	52.3 ²	62.2 ²	49.9 ²	10.4 ²
2	612.1 ³	1032.7 ³	544.2 ³	46.1	6.6
4	180.6	302.2	197.9	89.8	12.3
5	205.3	618.0	303.6	94.0	7.0
6	318.6	411.6	93.4	10.5	0.0
7	226.7	416.7	237.2	52.0	6.3
<u>Run 8809191355</u>					
3	325.7	273.2	146.2	77.6	20.9
<u>Run 8809191540</u>					
1	47.7 ²	32.4 ²	20.4 ²	12.4 ²	1.1 ²
2	541.1 ³	647.7 ³	336.4 ³	31.4	12.0
4	72.8	52.8	44.5	23.2	3.8
5	753.2	217.1	134.5	48.4	6.2
6	88.8	389.7	219.4	33.9	7.6
7	118.3	330.9	212.2	60.8	11.2

(Continued)

¹ Unless otherwise indicated, SD nozzles were used.² C nozzle used.³ D85 nozzle used.

(Sheet 2 of 3)

Table B2 (Concluded)

Trap No.	Streamer Number ¹				
	1	2	3	4	5
<u>Run 8809191610</u>					
3	194.9	122.3	91.7	28.0	9.6
<u>Run 8809191645</u>					
1	157.1	74.9	21.1	14.3	11.6
<u>Run 8809191715</u>					
1	133.5	48.9	15.6	5.4	4.8
<u>Run 8809211105</u>					
1	6.3 ²	0.0 ²	6.3 ²	7.0 ²	4.8 ²
2	237.7	44.6	54.2	46.1	11.5
3	120.3	49.0	32.9	16.7	6.2
4	93.8	19.6	12.9	9.5	7.3
5	550.9	51.7	22.5	20.8	3.4
6	46.1	52.1	37.3	19.7	5.3
7	316.2	39.3	19.8	14.3	6.9
<u>Run 8809211345</u>					
1	330.6 ²	127.6 ²	110.0 ²	20.0 ²	3.9 ²
2	1281.9	505.2	279.5	30.0	1.6
3	392.9	712.2	367.7	0.0	14.8
4	409.8	314.8	236.0	61.0	35.2
5	758.7	241.3	187.1	51.8	3.6
6	1003.4	763.4	231.8	3.1	1.9
7	236.6	423.8	225.0	59.1	0.0
<u>Run 8809211435</u>					
1	627.2	293.6	105.9	42.7	6.9
<u>Run 8809211520</u>					
1	1454.5 ²	621.4 ²	258.5 ²	5.4 ²	0.0 ²
2	517.1	116.1	42.6	17.3	3.2
3	57.8	24.3	7.2	8.6	10.8
4	6.9	4.7	6.4	2.2	0.0
5	59.9	10.3	4.7	1.9	0.0
6	62.3	5.3	4.7	5.4	0.0
7	93.6	7.9	7.8	0.5	0.0

¹ Unless otherwise indicated, SD nozzles were used.

² C nozzle used.

(Sheet 3 of 3)

Table B3

LUDINGTON: Streamer Elevations from Sea Bed to Mid-Streamer, m

<u>Trap No.</u>	<u>Streamer Number</u>				
	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>
<u>Run 8809141550</u>					
1	0.013	0.097	0.225	0.441	0.660
2	0.013	0.118	0.276	0.494	0.722
<u>Run 8809141610</u>					
3	0.013	0.095	0.224	0.435	0.656
<u>Run 8809161625</u>					
1	0.013	0.097	0.225	0.422	0.635
2	0.013	0.118	0.276	0.494	0.722
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.079	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.112	0.254	0.453	0.732
<u>Run 8809161725</u>					
1	0.013	0.097	0.225	0.422	0.635
2	0.013	0.118	0.276	0.494	0.722
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.205	0.429	0.722
<u>Run 8809171130</u>					
1	0.013	0.097	0.225	0.422	0.635
2	0.013	0.118	0.276	0.494	0.722
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.079	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.453	0.732
<u>Run 8809171521</u>					
1	0.026	0.103	0.203	0.432	0.663
2	0.013	0.118	0.276	0.494	0.722
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732

(Continued)

(Sheet 1 of 3)

Table B3 (Continued)

<u>Trap No.</u>	<u>Streamer Number</u>				
	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>
<u>Run 8809181525</u>					
1	0.026	0.103	0.203	0.432	0.663
2	0.013	0.118	0.276	0.494	0.722
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732
8	0.026	0.103	0.203	0.432	0.663
<u>Run 8809181645</u>					
1	0.026	0.103	0.203	0.432	0.663
2	0.013	0.118	0.276	0.494	0.722
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732
8	0.026	0.103	0.203	0.432	0.663
<u>Run 8809191325</u>					
1	0.026	0.103	0.203	0.432	0.663
2	0.045	0.172	0.326	0.515	0.747
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732
<u>Run 8809191355</u>					
3	0.013	0.095	0.224	0.435	0.656
<u>Run 8809191540</u>					
1	0.026	0.103	0.203	0.432	0.663
2	0.045	0.172	0.326	0.515	0.747
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732

(Continued)

(Sheet 2 of 3)

Table B3 (Concluded)

<u>Trap No.</u>	<u>Streamer Number</u>				
	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>5</u>
	<u>Run 8809191610</u>				
3	0.013	0.095	0.224	0.435	0.656
	<u>Run 8809191645</u>				
1	0.013	0.095	0.224	0.435	0.656
	<u>Run 8809191715</u>				
1	0.013	0.095	0.224	0.435	0.656
	<u>Run 8809211105</u>				
1	0.026	0.103	0.203	0.432	0.663
2	0.013	0.094	0.235	0.470	0.686
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732
	<u>Run 8809211345</u>				
1	0.026	0.103	0.203	0.432	0.663
2	0.013	0.094	0.235	0.470	0.686
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732
	<u>Run 8809211435</u>				
1	0.013	0.095	0.224	0.435	0.656
	<u>Run 8809211520</u>				
1	0.026	0.103	0.203	0.432	0.663
2	0.013	0.094	0.235	0.470	0.686
3	0.013	0.095	0.224	0.435	0.656
4	0.013	0.079	0.225	0.446	0.718
5	0.013	0.067	0.205	0.429	0.722
6	0.013	0.118	0.322	0.616	0.967
7	0.013	0.113	0.254	0.452	0.732

(Sheet 3 of 3)

Table B4

LUDINGTON: Water Levels

<u>Time</u> <u>EST¹</u>	<u>Water Level</u> <u>m. IGLD²</u>
<u>Run 8809141550</u>	
1500	176.309
1600	176.312
<u>Run 8809161625</u>	
1600	176.251
1700	176.284
<u>Run 8809161725</u>	
1700	176.284
1800	176.324
<u>Run 8809171130</u>	
1100	176.299
1200	176.318
<u>Run 8809171430</u>	
1400	176.312
1500	176.318
<u>Run 8809171521</u>	
1500	176.318
1600	176.333
<u>Run 8809171710</u>	
1700	176.324
1800	176.287
<u>Run 8809181525</u>	
1500	176.278
1600	176.287
<u>Run 8809181645</u>	
1600	176.287
1700	176.376
<u>Run 8809191325</u>	
1300	176.302
1400	176.302

(Continued)

(Sheet 1 of 2)

¹ Eastern Standard Time.² IGLD - International Great Lakes Datum (175.8 m IGLD - Low Water Datum (LWD)).

Table B4 (Concluded)

<u>Time</u> <u>EST</u>	<u>Water Level</u> <u>m. IGLD</u>
<u>Run 8809191540</u>	
1500	176.376
1600	176.302
<u>Run 8809191645</u>	
1600	176.302
1700	176.348
<u>Run 8809191715</u>	
1700	176.348
1800	176.409
<u>Run 8809211105</u>	
1100	176.275
1200	176.257
<u>Run 8809211345</u>	
1300	176.257
1400	176.245
<u>Run 8809211435</u>	
1400	176.245
1500	176.293
<u>Run 8809211520</u>	
1500	176.293
1600	176.333

Table B5

LUDINGTON: Current Meter Data

Time EDST ²	Current Speed, cm/sec							
	CY2 ¹		CX2		CY3		CX3	
	Mean	σ_v	Mean	σ_v	Mean	σ_v	Mean	σ_v
	<u>Run 8809141550</u>							
1550-1555	8.7	23.9	6.9	32.1	-1.9	23.8	4.3	33.7
	<u>Run 8809141610</u>							
1610-1615	9.1	24.0	6.0	33.2	-1.2	24.0	6.7	33.2
	<u>Run 8809141625</u>							
1625-1630	-15.8	38.4	9.3	47.1	-6.8	43.5	22.9	45.7
1630-1635	-16.8	40.7	11.7	51.4	-6.9	44.3	27.0	47.7
1635-1640	-19.0	34.4	8.4	46.5	-9.9	45.6	23.5	43.3
	<u>Run 8809161725</u>							
1725-1730	-15.9	34.7	4.2	45.0	-10.4	47.4	11.9	42.8
	<u>Run 8809171130</u>							
1130-1135	-9.7	113.2	7.8	117.0	-8.1	104.1	8.2	97.9
	<u>Run 8809171521</u>							
1521-1526	-11.0	47.9	0.3	53.1	0.7	51.3	1.7	49.0
	<u>Run 8809181525</u>							
1525-1530	-5.1	42.0	7.9	52.0	-5.9	44.1	4.7	49.7
1530-1532	2.8	35.7	13.2	45.3	-7.6	49.2	5.3	41.4
1534-1535	-5.7	38.3	7.9	54.3	-3.8	48.2	2.1	48.9
1535-1540	-3.7	39.8	11.3	55.6	-6.2	42.8	8.5	50.4
1540-1545	-2.5	39.9	7.3	51.2	-5.6	41.5	6.2	46.2
1545-1550	-2.0	40.2	7.6	50.2	-2.8	40.6	4.5	44.6

(Continued)

¹ Notation is defined in Appendix C.² Eastern Daylight Savings Time.

(Sheet 1 of 3)

Table B5 (Continued)

Time EDST	Current Speed, cm/sec							
	CY2		CX2		CY3		CX3	
	Mean	σ_v	Mean	σ_v	Mean	σ_v	Mean	σ_v
<u>Run 8809181645</u>								
1650-1655	-11.0	40.5	10.4	48.9	-5.1	34.6	11.2	36.5
1655-1700	-9.5	38.8	11.2	48.4	-5.5	35.6	9.6	39.1
1700-1702	-9.7	34.1	4.6	43.7	-7.4	33.1	4.7	36.7
1710-1715	-12.1	40.2	9.1	49.0	-5.7	40.2	7.1	41.7
<u>Run 8809191325</u>								
1325-1330	-35.6	39.6	16.5	61.4	-38.6	38.1	16.0	46.6
1330-1335	-10.5	40.3	20.2	65.9	-15.0	41.3	12.9	49.2
1335-1340	-30.3	38.5	15.8	62.8	-36.2	39.7	9.6	46.0
<u>Run 8809191355</u>								
1355-1356	-43.0	46.1	8.9	73.2	-36.0	41.4	17.7	45.4
1358-1405	-25.2	40.5	20.7	60.3	-31.5	40.1	16.8	48.1
<u>Run 8809191540</u>								
1540-1545	-26.2	38.9	6.8	54.8	-29.5	38.8	9.3	46.1
1545-1550	-28.9	36.9	13.7	55.8	-32.6	39.9	18.0	42.2
1550-1555	-26.5	38.5	13.8	57.6	-20.3	41.6	17.1	47.7
<u>Run 8809191610</u>								
1610-1615	-26.2	42.0	17.9	57.4	-29.0	41.1	17.0	49.1
<u>Run 8809191645</u>								
1645-1650	-12.9	38.5	21.7	67.6	-21.1	40.3	9.1	47.7
<u>Run 8809191715</u>								
1715-1720	-9.8	38.4	22.2	58.1	-13.8	40.8	14.3	43.8

(Continued)

(Sheet 2 of 3)

Table B5 (Concluded)

Time EDST	Current Speed, cm/sec							
	CY2		CX2		CY3		CX3	
	Mean	σ_v	Mean	σ_v	Mean	σ_v	Mean	σ_v
<u>Run 8809211105</u>								
1105-1110	2.5	31.2	7.8	32.1	-13.0	48.7	10.9	45.6
1110-1115	6.1	32.7	7.9	30.9	-15.6	49.4	5.0	40.4
1115-1120	10.0	31.0	8.8	32.7	-7.7	52.6	3.5	46.1
1120-1125	15.5	31.5	11.6	31.8	-12.4	50.4	4.6	42.5
1130-1135	9.2	32.3	12.6	32.3	-13.0	44.7	3.7	39.1
1135-1140	8.8	30.8	8.7	33.5	-14.9	46.8	2.3	40.8
<u>Run 8809211345</u>								
1347-1350	40.5	32.5	19.2	43.5	8.9	43.1	3.2	41.0
1350-1355	19.7	37.1	7.2	46.6	7.7	38.3	5.1	40.8
1355-1400	26.3	33.0	11.5	45.7	1.5	37.0	1.5	41.6
1400-1405	27.5	31.9	14.3	43.3	4.9	40.0	1.0	39.0
1405-1410	23.5	40.1	4.1	50.0	6.1	39.1	1.4	40.1
1410-1415	26.7	32.5	9.5	45.6	8.4	37.3	2.7	39.3
1415-1420	25.9	34.6	8.5	43.1	5.0	37.3	-0.9	39.2
<u>Run 8809211435</u>								
1435-1440	24.9	37.0	11.1	48.0	6.9	40.0	4.2	42.2
<u>Run 8809211520</u>								
1521-1525	2.5	36.3	3.0	39.5	3.8	45.6	1.6	41.4
<u>Run 8809211740</u>								
1740-1805	11.2	40.8	7.6	43.1	7.7	46.2	1.4	45.6

(Sheet 3 of 3)

Table B6
LUDINGTON: Wave Data

Run ID	Gage No.	Averaging Interval EDST ²	\bar{H}^1 m	σ_H m	H_{rms} m	$H_{1/3}$ m	$H_{1/10}$ m	H_{max} m	\bar{T} sec	σ_T sec	T_{rms} sec	$T_{1/3}$ sec	$T_{1/10}$ sec	T_{max} sec
8809141550	2	1550 - 1555	0.26	0.097	0.28	0.36	0.39	0.43	3.9	1.06	4.0	5.1	6.0	6.4
	3	1550 - 1555	0.28	0.102	0.30	0.39	0.43	0.49	3.9	1.07	4.1	5.0	5.7	6.2
8809141610	2	1610 - 1615	0.26	0.108	0.28	0.37	0.44	0.48	3.8	1.41	4.0	5.3	6.5	7.6
	3	1610 - 1615	0.24	0.097	0.26	0.35	0.42	0.47	3.6	1.11	3.7	4.8	5.6	6.0
8809161625	1	1625 - 1630	0.27	0.099	0.29	0.38	0.43	0.46	4.4	1.62	4.7	6.2	7.7	9.6
	2	1625 - 1630	0.23	0.105	0.25	0.34	0.40	0.49	4.3	1.59	4.6	6.1	6.8	8.4
	3	1625 - 1630	0.25	0.102	0.27	0.36	0.44	0.60	4.3	1.53	4.5	6.0	6.9	7.6
	1	1630 - 1635	0.28	0.092	0.29	0.38	0.44	0.47	4.7	1.24	4.8	6.0	6.7	7.6
	2	1630 - 1635	0.24	0.105	0.26	0.36	0.40	0.43	4.2	1.53	4.5	5.9	6.9	7.4
	3	1630 - 1635	0.24	0.098	0.26	0.35	0.39	0.40	4.2	1.66	4.5	6.1	7.3	8.6
	1	1635 - 1640	0.25	0.110	0.27	0.33	0.47	0.52	4.5	1.49	4.8	6.3	7.2	7.8
	2	1635 - 1640	0.25	0.096	0.26	0.34	0.40	0.53	4.6	1.58	4.9	6.4	7.2	8.6
	3	1635 - 1640	0.27	0.104	0.29	0.38	0.44	0.47	4.6	1.78	4.9	6.6	7.5	8.8
8809161725	2	1725 - 1730	0.20	0.092	0.22	0.30	0.38	0.43	4.6	1.65	4.9	6.4	7.2	8.2
	3	1725 - 1730	0.25	0.113	0.27	0.37	0.48	0.54	5.0	1.91	5.4	7.1	8.5	10.8
8809171130	1	1130 - 1135	0.18	0.078	0.20	0.26	0.33	0.42	3.8	1.23	4.0	5.1	5.7	6.6
	2	1130 - 1135	0.20	0.083	0.22	0.30	0.33	0.37	3.8	1.17	4.0	5.1	6.0	6.8
	3	1130 - 1135	0.23	0.068	0.24	0.30	0.36	0.44	4.1	1.15	4.3	5.4	6.2	8.4
8809171521	1	1521 - 1526	0.24	0.141	0.27	0.37	0.55	0.85	3.9	1.41	4.1	5.5	6.7	8.4
	2	1521 - 1526	0.23	0.098	0.25	0.34	0.43	0.54	4.0	1.21	4.2	5.4	6.2	7.0
	3	1521 - 1526	0.23	0.127	0.26	0.36	0.49	0.80	3.6	1.33	3.9	5.1	6.1	7.0
8809181525	1	1525 - 1530	0.17	0.081	0.19	0.27	0.34	0.42	3.7	1.23	3.9	5.0	6.4	8.2
	2	1525 - 1530	0.27	0.102	0.28	0.38	0.45	0.53	3.7	1.04	3.8	4.8	5.6	8.0
	3	1525 - 1530	0.21	0.085	0.22	0.29	0.38	0.51	3.6	0.93	3.7	4.7	5.3	5.6
	1	1530 - 1532	0.14	0.078	0.16	0.22	0.33	0.43	3.4	1.03	3.5	4.5	5.4	6.4
	2	1530 - 1531	0.32	0.111	0.34	0.43	0.57	0.57	4.0	1.02	4.1	5.1	5.6	5.6
	3	1530 - 1531	0.25	0.100	0.27	0.37	0.45	0.45	4.2	1.05	4.1	5.2	5.8	5.8
	1	1534 - 1535	0.17	0.107	0.20	0.31	0.38	0.38	3.6	0.66	3.7	4.3	4.4	4.4
	2	1534 - 1535	0.25	0.130	0.28	0.41	0.50	0.50	3.1	0.60	3.2	3.9	4.0	4.0
	3	1534 - 1535	0.22	0.094	0.24	0.33	0.37	0.37	3.4	0.88	3.5	4.3	5.0	5.0
	1	1535 - 1540	0.17	0.086	0.19	0.26	0.35	0.55	3.7	1.35	3.9	5.2	6.4	10.4
	2	1535 - 1540	0.27	0.101	0.29	0.38	0.45	0.54	3.7	1.07	3.9	4.9	5.7	7.2
	3	1535 - 1540	0.23	0.086	0.24	0.32	0.39	0.43	3.8	1.07	4.0	5.0	6.0	6.6
	1	1540 - 1545	0.15	0.074	0.17	0.23	0.32	0.46	3.6	1.07	3.7	4.7	5.8	7.0
	2	1540 - 1545	0.27	0.104	0.29	0.38	0.46	0.71	3.7	1.03	3.9	4.9	5.6	6.6
	3	1540 - 1545	0.22	0.098	0.24	0.32	0.41	0.69	3.6	0.93	3.7	4.6	5.1	5.4
	1	1545 - 1550	0.15	0.068	0.17	0.23	0.28	0.38	3.2	0.91	3.3	4.2	5.0	5.8
	2	1545 - 1550	0.24	0.081	0.25	0.33	0.38	0.42	3.7	1.01	3.8	4.9	5.7	7.0
	3	1545 - 1550	0.20	0.101	0.23	0.32	0.41	0.50	3.5	0.98	3.6	4.6	5.5	6.6
8809181645	1	1650 - 1655	0.18	0.103	0.20	0.29	0.39	0.64	3.4	0.98	3.5	4.4	5.1	6.2
	2	1650 - 1655	0.23	0.090	0.25	0.33	0.39	0.44	3.6	0.88	3.7	4.5	5.0	6.0
	3	1650 - 1655	0.21	0.084	0.22	0.30	0.35	0.42	3.5	0.89	3.6	4.5	5.2	6.0
	1	1655 - 1700	0.15	0.077	0.17	0.24	0.31	0.41	3.4	0.86	3.5	4.4	4.9	5.2
	2	1655 - 1700	0.23	0.095	0.24	0.34	0.40	0.45	3.4	0.96	3.6	4.4	5.1	7.4
	3	1655 - 1700	0.22	0.093	0.24	0.33	0.40	0.43	3.4	0.89	3.5	4.3	5.0	6.8
	1	1700 - 1705	0.15	0.093	0.18	0.25	0.37	0.53	3.5	0.99	3.6	4.5	5.6	6.8
	2	1700 - 1701	0.15	0.079	0.17	0.24	0.29	0.29	3.3	0.92	3.4	4.3	4.6	4.6
	3	1700 - 1701	0.14	0.080	0.16	0.23	0.28	0.28	3.2	0.77	3.3	4.1	4.4	4.4
	1	1705 - 1709	0.15	0.074	0.17	0.24	0.32	0.40	3.5	0.80	3.6	4.4	5.0	5.4
	2	1710 - 1715	0.20	0.078	0.22	0.29	0.34	0.40	3.5	1.08	3.7	4.7	5.8	8.4
	3	1710 - 1715	0.20	0.091	0.22	0.30	0.37	0.48	3.4	0.91	3.5	4.4	5.1	6.0

(Continued)

¹ Notation is defined in Appendix C.
² Eastern Daylight Savings Time.

Table B6 (Concluded)

Run ID	Gage No.	Averaging Interval EDST	\bar{H} m	σ_H m	H_{rms} m	$H_{1/3}$ m	$H_{1/10}$ m	H_{max} m	\bar{T} sec	σ_T sec	T_{rms} sec	$T_{1/3}$ sec	$T_{1/10}$ sec	T_{max} sec
8809191325	2	1325 - 1330	0.31	0.140	0.34	0.46	0.58	0.71	4.3	1.79	4.7	6.4	7.9	10.2
	3	1325 - 1330	0.28	0.126	0.30	0.41	0.52	0.66	4.2	1.73	4.5	6.3	7.5	9.0
	2	1330 - 1335	0.34	0.151	0.37	0.51	0.62	0.86	4.8	1.92	5.1	7.1	8.5	9.4
	3	1330 - 1335	0.29	0.143	0.32	0.46	0.54	0.62	4.4	1.85	4.8	6.6	8.1	9.4
	2	1335 - 1340	0.31	0.144	0.35	0.48	0.58	0.64	4.4	2.09	4.9	6.9	8.6	9.8
	3	1335 - 1340	0.28	0.146	0.32	0.46	0.585	0.61	4.4	1.91	4.8	6.7	8.0	8.8
8809191355	2	1358 - 1405	0.32	0.128	0.34	0.46	0.53	0.59	4.5	1.81	4.8	6.5	7.6	8.6
	3	1358 - 1405	0.29	0.141	0.32	0.44	0.56	0.71	4.4	1.65	4.7	6.2	7.6	9.0
8809191540	2	1540 - 1545	0.31	0.143	0.34	0.46	0.55	0.85	4.5	2.00	4.9	6.9	8.2	9.2
	3	1540 - 1545	0.31	0.135	0.33	0.47	0.55	0.60	4.7	2.16	5.2	7.4	8.9	10.0
	2	1545 - 1550	0.33	0.135	0.36	0.48	0.54	0.58	4.8	1.89	5.1	6.8	8.2	9.4
	3	1545 - 1550	0.27	0.139	0.31	0.43	0.53	0.76	4.1	1.93	4.5	6.4	7.9	9.6
	2	1550 - 1555	0.34	0.147	0.37	0.50	0.62	0.75	4.7	2.09	5.2	7.3	8.8	9.6
	3	1550 - 1555	0.31	0.130	0.33	0.45	0.54	0.58	4.3	1.81	4.7	6.5	8.1	8.8
8809191610	2	1610 - 1615	0.35	0.141	0.38	0.51	0.57	0.65	4.8	2.01	5.2	7.2	8.3	10.0
	3	1610 - 1615	0.29	0.124	0.32	0.43	0.54	0.69	4.3	1.81	4.7	6.5	8.0	10.2
8809191645	2	1645 - 1650	0.32	0.124	0.34	0.47	0.54	0.57	4.6	2.05	5.0	7.1	8.2	9.2
	3	1645 - 1650	0.31	0.149	0.35	0.48	0.59	0.67	4.5	2.13	5.0	7.0	9.1	11.2
8809191715	2	1715 - 1720	0.30	0.133	0.33	0.45	0.52	0.55	4.5	2.47	5.1	7.4	9.8	13.0
	3	1715 - 1720	0.30	0.133	0.33	0.46	0.52	0.60	5.0	2.51	5.6	8.0	10.1	13.8
8809211105	2	1105 - 1110	0.21	0.083	0.23	0.30	0.36	0.42	3.7	1.29	3.9	5.2	6.5	7.8
	3	1105 - 1110	0.21	0.089	0.23	0.32	0.39	0.47	3.5	1.04	3.6	4.6	5.5	6.4
	2	1110 - 1115	0.22	0.086	0.24	0.32	0.37	0.42	4.0	1.36	4.2	5.5	6.9	8.0
	3	1110 - 1115	0.22	0.092	0.24	0.32	0.38	0.47	3.8	1.35	4.1	5.3	6.7	8.8
	2	1115 - 1120	0.22	0.082	0.23	0.31	0.37	0.41	3.9	1.39	4.2	5.5	6.9	8.6
	3	1115 - 1120	0.20	0.074	0.21	0.28	0.34	0.47	3.7	1.44	4.0	5.3	7.1	8.8
	2	1120 - 1125	0.22	0.082	0.23	0.30	0.37	0.60	3.8	1.14	3.9	5.0	6.1	8.6
	3	1120 - 1125	0.20	0.081	0.22	0.29	0.34	0.42	3.5	1.32	3.7	4.8	6.2	11.4
	2	1125 - 1130	0.21	0.078	0.23	0.30	0.36	0.39	3.9	1.41	4.2	5.5	7.2	8.8
	3	1125 - 1130	0.21	0.076	0.22	0.29	0.33	0.39	3.6	1.35	3.8	5.1	6.5	8.8
	2	1130 - 1135	0.20	0.108	0.22	0.31	0.43	0.76	3.4	1.20	3.6	4.8	5.9	6.6
	3	1130 - 1135	0.19	0.086	0.21	0.28	0.36	0.51	3.6	1.49	3.9	5.2	6.9	9.8
	2	1135 - 1140	0.21	0.084	0.22	0.30	0.34	0.40	3.6	1.35	3.8	5.1	6.3	8.6
	3	1135 - 1140	0.20	0.098	0.22	0.29	0.40	0.64	3.5	1.33	3.7	5.0	6.4	8.4
	8809211345	2	1347 - 1350	0.20	0.064	0.21	0.27	0.32	0.40	3.8	1.32	4.0	5.4	6.4
3		1347 - 1350	0.19	0.066	0.20	0.26	0.32	0.34	3.9	1.30	4.1	5.4	6.5	7.4
2		1350 - 1355	0.21	0.078	0.23	0.29	0.36	0.43	3.7	1.20	3.9	5.1	6.1	7.0
3		1350 - 1355	0.20	0.067	0.21	0.27	0.32	0.35	3.8	1.15	3.9	5.1	5.9	6.6
2		1355 - 1400	0.23	0.108	0.26	0.33	0.46	0.74	3.7	1.18	3.9	5.0	5.6	6.8
3		1355 - 1400	0.22	0.080	0.23	0.31	0.37	0.44	3.8	1.27	4.0	5.2	6.0	6.6
2		1400 - 1405	0.20	0.075	0.21	0.29	0.33	0.40	3.5	1.23	3.7	4.9	6.0	7.0
3		1400 - 1405	0.21	0.074	0.22	0.28	0.32	0.35	3.9	1.40	4.1	5.4	6.3	7.8
2		1405 - 1410	0.22	0.094	0.24	0.31	0.39	0.57	3.6	1.25	3.8	4.9	5.9	7.2
3		1405 - 1410	0.21	0.085	0.23	0.30	0.37	0.51	3.9	1.23	4.0	5.2	5.8	6.4
2		1410 - 1415	0.21	0.075	0.23	0.29	0.34	0.45	3.6	1.23	3.8	5.0	6.1	7.0
3		1410 - 1415	0.20	0.076	0.21	0.28	0.33	0.44	3.7	1.18	3.9	5.0	5.6	6.8
2		1415 - 1420	0.19	0.074	0.21	0.28	0.32	0.37	3.5	1.15	3.7	4.8	5.7	7.6
3		1415 - 1420	0.17	0.072	0.19	0.25	0.29	0.31	3.4	1.04	3.6	4.6	5.2	6.0
8809211435		2	1435 - 1440	0.22	0.080	0.23	0.30	0.38	0.48	3.9	1.24	4.1	5.3	6.1
	3	1435 - 1440	0.21	0.079	0.23	0.29	0.35	0.44	3.7	1.18	3.8	5.0	5.6	5.8
8809211520	2	1521 - 1525	0.19	0.072	0.20	0.27	0.32	0.47	3.8	1.30	4.0	5.3	6.0	6.6
	3	1521 - 1525	0.21	0.073	0.22	0.29	0.33	0.38	4.1	1.19	4.2	5.3	6.1	6.8

(Sheet 2 of 2)

Table B7

LUDINGTON: Profile Survey Data

<u>Profile Line</u> <u>No.</u>	<u>Distance from</u> <u>Baseline, m</u>	<u>Elevation</u> <u>m LWD¹</u>
	<u>September 14²</u>	
22 ³	0.0	1.89
	3.0	1.46
	6.1	1.34
	9.1	1.34
	12.2	1.28
	15.2	1.19
	18.3	1.13
	21.3	1.07
	24.4	0.58
	27.4	0.24
	30.5	0.15
	33.5	0.03
	36.6	-0.09
	39.6	-0.27
	42.7	-0.40
	45.7	-0.52
	48.8	-0.61
	51.8	-0.67
	54.9	-0.70
	57.9	-0.76
	61.0	-0.76
	64.0	-0.76
	67.1	-0.70
	70.1	-0.67
	73.2	-0.64
	76.2	-0.58
	79.3	-0.58
	82.3	-0.58
	85.4	-0.58
	88.4	-0.49
	91.4	-0.46
	94.5	-0.46
	97.5	-0.52

(Continued)

¹ LWD = Low Water Datum.² Traps positioned approximately halfway between profile lines 22 and 24 on 14 September.³ Profile line 22 intersects the baseline at state plane coordinates 91,121.0 m East and 285,268.4 m North, and is directed offshore at an azimuth 270° 14' 31'' from North.

(Sheet 1 of 4)

Table B7 (Continued)

<u>Profile Line No.</u>	<u>Distance from Baseline, m</u>	<u>Elevation m LWD</u>
<u>September 14</u>		
24 ¹	0.0	1.80
	3.0	1.52
	6.1	1.34
	9.1	1.16
	12.2	1.07
	15.2	1.04
	18.3	0.98
	21.3	0.18
	24.4	0.24
	27.4	0.15
	30.5	0.00
	33.5	-0.15
	36.6	-0.34
	39.6	-0.46
	42.7	-0.61
45.7	-0.73	
48.8	-0.82	
51.8	-0.98	
54.9	-1.04	
<u>September 16²</u>		
23 ³	0.0	-
	3.0	-
	6.1	-
	9.1	-
	12.2	-
	15.2	1.13
	18.3	1.04
	21.3	0.73
	24.4	0.37
	27.4	0.09
30.5	-0.09	

(Continued)

¹ Profile line 24 intersects the baseline at state plane coordinates 91,121.1 m East and 285,298.9 m North, and is directed offshore at an azimuth 270° 14' 31'' from North.

² Traps positioned at profile line indicated for succeeding dates.

³ Profile line 23 intersects the baseline at state plane coordinates 91,121.1 m East and 285,283.6 m North, and is directed offshore at an azimuth 270° 14' 31'' from North.

(Sheet 2 of 4)

Table B7 (Continued)

<u>Profile Line</u> <u>No.</u>	<u>Distance from</u> <u>Baseline, m</u>	<u>Elevation</u> <u>m LWD</u>
	<u>September 17</u>	
	33.5	-0.24
	36.6	-0.34
	39.6	-0.46
	42.7	-0.55
	45.7	-0.64
	48.8	-0.73
	51.8	-0.79
23	0.0	1.62
	3.0	1.37
	6.1	1.34
	9.1	1.37
	12.2	1.31
	15.2	1.13
	18.3	1.10
	21.3	1.07
	24.4	1.07
	27.4	0.61
	30.5	0.27
	33.5	0.09
	36.6	-0.27
	39.6	-0.46
	42.7	-0.55
	45.7	-0.67
	48.8	-0.73
	<u>September 18</u>	
23	0.0	-
	3.0	-
	6.1	-
	9.1	-
	12.2	-
	15.2	1.10
	18.3	1.07
	21.3	1.04
	24.4	1.07
	27.4	0.98
	30.5	0.61
	33.5	0.24
	36.6	0.03

(Continued)

(Sheet 3 of 4)

Table B7 (Concluded)

<u>Profile Line</u> <u>No.</u>	<u>Distance from</u> <u>Baseline, m</u>	<u>Elevation</u> <u>m LWD</u>
	39.6	-0.40
	42.7	-0.58
	45.7	-0.67
<u>September 21</u>		
20 ¹	0.0	2.07
	3.0	1.77
	6.1	1.52
	9.1	1.37
	12.2	1.37
	15.2	1.31
	18.3	1.37
	21.3	1.40
	24.4	1.49
	27.4	1.46
	30.5	0.98
	33.5	0.55
	36.6	0.30
	39.6	0.09
	42.7	-0.03
	45.7	-0.46
	48.8	-0.58
	51.8	-0.67
	54.9	-0.67
	57.9	-0.70
	61.0	-0.67

¹ Profile line 20 intersects the baseline at state plane coordinates 91,120.9 m East and 285,237.9 m North, and is directed offshore at an azimuth 270° 14' 31'' from North. (Sheet 4 of 4)

Table B8

LUDINGTON: Grain Size Statistics

Run ID and Trap No.	Streamer No.	Moment Statistics				Folk Inclusive Graphic Statistics				
		First PHI	Second PHI	Third	Fourth	Median PHI	Mean PHI	Standard Deviation PHI	Skewness	Kurtosis
8809181525 3	1	1.61	0.30	0.18	4.69	1.62	1.62	0.30	-0.06	1.07
	2	1.74	0.27	0.03	4.04	1.74	1.74	0.26	0.01	1.05
	3	1.71	0.30	-0.42	3.82	1.72	1.71	0.29	-0.07	1.12
	4	1.58	0.31	-0.08	3.64	1.60	1.59	0.32	-0.07	2.06
	5	1.90	0.47	0.74	4.15	1.85	1.87	0.44	0.21	1.58
8809191355 3	1	1.55	0.29	-0.41	3.06	1.58	1.56	0.30	-0.13	1.03
	2	1.66	0.25	-0.36	3.95	1.66	1.66	0.25	-0.05	1.10
	3	1.66	0.25	-0.46	3.58	1.67	1.66	0.26	-0.09	1.06
	4	1.68	0.25	-0.42	3.80	1.69	1.69	0.24	-0.05	1.02
	5	1.67	0.26	-0.42	3.59	1.68	1.67	0.26	-0.08	1.06
8809191610 3	1	1.61	0.26	-0.41	4.61	1.63	1.62	0.26	-0.12	1.16
	2	1.66	0.24	-0.42	4.61	1.66	1.67	0.23	-0.04	1.05
	3	1.67	0.24	-0.39	4.25	1.67	1.68	0.23	-0.03	1.02
	4	1.67	0.25	-0.33	4.59	1.68	1.68	0.24	-0.03	1.02
	5	1.68	0.27	-0.48	5.25	1.69	1.69	0.26	-0.08	1.08
8809191645 3	1	1.62	0.26	-0.45	3.50	1.64	1.63	0.27	-0.12	1.04
	2	1.69	0.24	-0.37	3.75	1.70	1.70	0.24	-0.05	1.00
	3	1.71	0.24	-0.37	3.74	1.72	1.72	0.23	-0.03	1.03
	4	1.73	0.23	-0.31	3.92	1.74	1.73	0.23	-0.04	1.03
	5	1.71	0.25	-0.41	3.83	1.72	1.73	0.24	-0.03	1.04
8809211105 3	1	1.48	0.34	-0.28	2.78	1.52	1.48	0.35	-0.18	1.00
	2	1.60	0.31	-0.43	3.19	1.63	1.61	0.31	-0.14	1.01
	3	1.59	0.30	-0.39	3.13	1.61	1.60	0.31	-0.13	0.99
	4	1.62	0.31	-0.42	3.21	1.64	1.62	0.32	-0.12	1.05
	5	1.59	0.31	-0.35	3.40	1.62	1.60	0.32	-0.12	1.03

APPENDIX C: NOTATION

C	Cube nozzle, 5.1 cm high, 5.1 cm wide, 5.1 cm hood
CM1	Current Meter 1
CM2	Current Meter 2
CM3	Current Meter 3
COM	Comparison test between two different closely-spaced devices
CON	Consistency test between two closely-spaced traps
CX1	Cross-shore component of current speed at current meter 1
CX2	Cross-shore component of current speed at current meter 2
CX3	Cross-shore component of current speed at current meter 3
CY1	Longshore component of current speed at current meter 1
CY2	Longshore component of current speed at current meter 2
CY3	Longshore component of current speed at current meter 3
D85	DUCK85 nozzle, 9 cm high, 15 cm wide
\bar{H}	Mean wave height, m
H_{max}	Maximum wave height, m
H_{min}	Minimum wave height, m
H_{mo}	Spectrally-based significant wave height, m
H_{rms}	Root-mean-square wave height, m
$H_{1/3}$	Significant wave height, average of the highest one-third wave heights, m
$H_{1/10}$	Average of the highest one-tenth wave heights, m
OBS	Optical Backscatter Sensor
PG1	Pressure Gage 1
PG2	Pressure Gage 2
PG3	Pressure Gage 3
SD	SUPERDUCK nozzle, 2.5 cm high, 15 cm wide, and 5.1 cm hood
SSM	Spatial Sampling Method
\bar{T}	Mean wave period, sec
T_{max}	Maximum wave period, sec
T_p	Spectral peak wave period, sec
T_{rms}	Root-mean-square wave period, sec
TSM	Temporal Sampling Method
$T_{1/3}$	Average of the longest one-third wave periods, sec

$T_{1/10}$	Average of the longest one-tenth wave periods, sec
x	Distance offshore, m
y	Distance alongshore, m
σ_H	Standard deviation in wave height, m
σ_T	Standard deviation in wave period, sec
σ_v	Standard deviation in current speed, cm/sec